Your Mission: Use F-Response to collect Amazon S3 Bucket data



Using F-Response to collect Amazon S3 Storage Bucket contents

Mission Guide: Amazon S3

i

Note

Disclaimer: F-Response provide access to 3rd party data sources via Application Programming Interfaces (APIs) and internal structures presented by the provider. 3rd party provided data sources by their very nature are volatile. The afore mentioned F-Response **Important** products provide "best effort" for accessing and interacting with those 3rd party data sources however service disruptions, API changes, provider errors, network errors, as well as other communications issues may result in errors or incomplete data access. F-Response always recommends secondary validation of any 3rd party data collection.

F-Response Cloud Coll	lector Options Supported					
Revision History	Not available.	Amazon S3 does not support revision history. Enabling Revision History in F-Response				
		will have no effect on the collection.				
Hash Verification	Available and	Amazon S3 provides md5 hashes of items which will be automatically checked in F-				
	supported.	Response if Verify Hashes is enabled. NOTE Hashes for Multi-part uploads will not				
		be verified.				

Step 1: Open the Amazon S3 Credential **Configuration Window**

Open the F-Response Management Console and navigate to Cloud->Add Cloud Credential->Amazon S3, or double click on the appropriate icon in the Data Sources pane.



F-Response Management Console

Step 2: Obtain Amazon S3 Credentials

Amazon S3 Storage Credentials are found on the Amazon AWS Console (see **aws.amazon.com**). The specific credentials required are available under the "**Security Credentials**" link under **My Account**, see below:



Amazon Web Services Main Page

Locate the **Access Credentials** section and record (copy/paste) **the Access Key ID**, then click "**Show**" to open a secondary window containing the **Secret Access Key**.

Access Credentials

There are three types of access credentials used to authenticate your requests to AWS services: (a) access keys, (b) X.509 certificates, and (c) key pairs. Each access credential type is explained below.

Access Keys	🗟 X.509 Certificates 🕅 k	(ey Pairs					
Use access keys to make secure REST or Query protocol requests to any AWS service API. We create one for you when your account is created — see your access key below.							
Created	Access Key ID	Secret Access Key	Status				
August 19, 2010	agh423jka941dlt0438	Show	Active (Make Inactive)				
Create a new Access Key							

Amazon AWS Access Key and Secret Access Key

The preceding credentials (Access Key and Secret Key) must be entered in the corresponding fields in the **Configure Amazon S3 Credentials** dialog. The Name field is **not** optional and is used to provide a secondary human readable identifier for the credential set (Ex "Client X Account").

mazon Simple Storage S	rvice (S3) Credentials	
Name		
Access Key		
Secret Key		
L		
	Ac	dd Cancel

Configure S3 Credentials

Step 3: Start a collection

Select the Amazon S3 Bucket icon under Data Sources and then double click on the newly added Amazon S3 account under Items. This will prepare a new dialog for collecting a bucket's contents.

	Bucket		^
- Rudut	s3-standard		
Bucket	s3-jumbo		
	s3-empty		~
Collection Type	L		
	Collect to local VHD O	Collect to local directory	
C <mark>ollection Pat</mark> h	J:\amztest		
Total Available S	bace = 58744MB		
Total Available a	pace - boy timb		

Starting a new collection

Select the specific bucket you would like to collect, as well as whether you would like to collect the bucket to a virtual hard disk or a local directory. In either case a collection of the bucket contents will be made, along with a log file and error file to indicate any errors that might have occurred during the collection.

Step 4: Check the Activity Pane

The Activity Pane shows the active collection. Double clicking on the collection will provide additional details.

	pending
	Active Collections
oud Collectio	on Activity Details
Name	s3-standard-AMZ Test Cred-AmazonS3-9-17-2018-17-47-5:
Target	s3-standard
State	collecting
Region	s3-standard.s3.amazonaws.com
Destination	\\?\GLOBALROOT\Device\HarddiskVolume10
Performance	2433kbps
	Developeding item \ED espenses Latest\E
Last Message	ResponseTACTICAL-4.0.0.3-EN.zip
	~
Duration	0000:00:33
	77252046
Total Bytes	77253540
	6

Collection Details...

Step 5: Review the Completed Collection

Navigate to the destination folder at the completion of the collection to review the individual files collected, or the summary VHD, along with any log or error reports.

1	M	а	m	e .
		ų	111	~

	_		-	_		
 \sim						

Name	Date modified	Туре
AMZ Test Cred-AmazonS3-9-17-2018-17-48-45.csv	9/17/2018 1:50 PM	CSV File
AMZ Test Cred-AmazonS3-parse-errors-9-17-2018-17-48-45.csv	9/17/2018 1:48 PM	CSV File
s3-standard-AMZ Test Cred-AmazonS3-9-17-2018-17-47-53.vhd	9/17/2018 1:50 PM	Hard Disk Image F

Reviewing the completed image.

Additional Details

The following file datetime values are used by F-Response during the collection (Any missing dates are set to 1601-01-01T00:00:01Z):

WINDOWS TIME	PROVIDER VALUE
MODIFIED	LastModified
ACCESSED	
CREATED	

Troubleshooting

I have valid S3 Credentials however I get no buckets returned, why?

Most likely your computer's clock is too far skewed from the current time. Your examiner machine's clock must be accurate to within 15 minutes of actual time. The time zone is un-important.